

Package: rawKS (via r-universe)

September 5, 2024

Title Easily Get True-Positive Rate and False-Positive Rate and KS
Statistic

Version 0.1.0

Description The Kolmogorov-Smirnov (K-S) statistic is a standard method to measure the model strength for credit risk scoring models. This package calculates the K-S statistic and plots the true-positive rate and false-positive rate to measure the model strength. This package was written with the credit marketer, who uses risk models in conjunction with his campaigns. The users could read more details from Thrasher (1992) [doi:10.1002/dir.4000060408](https://doi.org/10.1002/dir.4000060408) and 'pyks' <https://pypi.org/project/pyks/>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports dplyr, magrittr, ROCR, ggplot2, tidyr

Roxygen list(markdown = TRUE)

RoxygenNote 6.1.1

Depends R (>= 2.10)

Suggests knitr, rmarkdown

VignetteBuilder knitr

Repository <https://jiaxiangbu.r-universe.dev>

RemoteUrl <https://github.com/jiaxiangbu/rawks>

RemoteRef HEAD

RemoteSha 37b24cfc2c40e339bd808f16ec914427f35f58dd

Contents

ks_plot	2
ks_table	2
two_class_example_edited	3

Index[4](#)

ks_plot	<i>Plot KS chart</i>
---------	----------------------

Description

Plot KS chart

Usage

```
ks_plot(df)
```

Arguments

df data.frame created by ks_table

Value

The 'ggplot2' object

Examples

```
data("two_class_example_edited")
max(ks_table(two_class_example_edited$yhat, two_class_example_edited$y)$ks)
ks_table(two_class_example_edited$yhat, two_class_example_edited$y) %>%
  ks_plot()
```

ks_table	<i>Get KS statistics</i>
----------	--------------------------

Description

Output a data.frame with inputs (y, yhat) and tpr, fpr and ks.

Usage

```
ks_table(yhat, y)
```

Arguments

yhat numeric the value predicted by your model.
y numeric the target values.

Value

The data frame containing tpr, fpr and ks.

Examples

```
data("two_class_example_edited")
max(ks_table(two_class_example_edited$yhat, two_class_example_edited$y)$ks)
```

`two_class_example_edited`

A sample with the target and predictions

Description

A dataset containing two columns, `yhat` and `y` as the inputs for the function `ks_table`.

Usage

```
two_class_example_edited
```

Format

A data frame with 500 rows and 2 variables:

yhat predictions

y target

Source

package `yardstick`::`two_class_example`

Index

* datasets

two_class_example_edited, 3

ks_plot, 2

ks_table, 2

two_class_example_edited, 3